

我應該如何編寫VEE程式，以便
在.NET環境中輕易地使用這些程
式？

Notices

© Keysight Technologies Incorporated, 2002-2020

1400 Fountaingrove Pkwy., Santa Rosa, CA 95403-1738, United States All rights reserved.

No part of this documentation may be reproduced in any form or by any means (including electronic storage and retrieval or translation into a foreign language) without prior agreement and written consent from Keysight Technologies, Inc. as governed by United States and international copyright laws.

Restricted Rights Legend

If software is for use in the performance of a U.S. Government prime contract or subcontract, Software is delivered and licensed as "Commercial computer software" as defined in DFAR 252.227-7014 (June 1995), or as a "commercial item" as defined in FAR 2.101(a) or as "Restricted computer software" as defined in FAR 52.227-19 (June 1987) or any equivalent agency regulation or contract clause.

Use, duplication or disclosure of Software is subject to Keysight Technologies' standard commercial license terms, and non-DOD Departments and Agencies of the U.S. Government will receive no greater than Restricted Rights as defined in FAR 52.227-19(c)(1-2) (June 1987). U.S. Government users will receive no greater than Limited Rights as defined in FAR 52.227-14 (June 1987) or DFAR 252.227-7015 (b)(2) (November 1995), as applicable in any technical data.

Portions of this software are licensed by third parties including open source terms and conditions.

For detail information on third party licenses, see [Notice](#).

我應該如何編寫VEE程式，以便在.NET環境中輕易地使用這些程式？

Contents

我應該如何編寫VEE程式，以便在.NET環境中輕易地使用這些程式？

現在您可以執行四件事來加強您的VEE 6.1程式碼的品質，以便往後在Visual Studio .NET中使用。

設計您的VEE程式結構，以充份利用UserFunctions。只有UserFunctions或UserFunctions中的內嵌物，可以從.NET中存取。Main則無法從.NET中存取。UserObjects只有內嵌在UserFunction中，才能被存取。

請確定參數名稱是描述性的，並遵守Visual Studio .NET所要求的文數字命名規則；參數名稱的第一個字元是字母，而且名稱只能包含字母、數字和底線。

在Object功能表中，為每個UserFunction選擇Description。為每個UserFunction編寫一個完整的描述。如果您習慣使用XML，也可以輸入XML <summary>資訊和<param name="parameter">資訊。當您從.NET存取時，這個XML會被擷取，並會為VEE UserFunction提供IntelliSense。

針對UserFunction的每個輸入參數，開啟Input Terminal Constraints。將資料類型和形狀設為明確的值。

